

Package: matrixcut (via r-universe)

June 2, 2026

Version 0.0.1

Date 2023-03-19

Title Determines Clustering Threshold Based on Similarity Values

Maintainer Matthew Cserhati <csmaty@protonmail.com>

Description The user must supply a matrix filled with similarity values. The software will search for significant differences between similarity values at different hierarchical levels. The algorithm will return a Loess-smoothed plot of the similarity values along with the inflection point, if there are any. There is the option to search for an inflection point within a specified range. The package also has a function that will return the matrix components at a specified cutoff. References: Mullner. <ArXiv:1109.2378>; Cserhati, Carter. (2020, Journal of Creation 34(3):41-50), <https://dl0.creation.com/articles/p137/c13759/j34-3_64-73.pdf>.

License GPL (>= 3)

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Imports igraph, stats, inflection

NeedsCompilation no

Author Matthew Cserhati [aut, cre]
(<<https://orcid.org/0000-0002-3673-9152>>)

Depends R (>= 3.5.0)

Config/pak/sysreqs libgmp-dev libxml2-dev

Repository <https://csmaty.r-universe.dev>

Date/Publication 2023-03-24 15:30:02 UTC

RemoteUrl <https://github.com/cran/matrixcut>

RemoteRef HEAD

RemoteSha 166ead04638609c26ecee528a359f79a32fad06

Contents

componentplot	2
cutoffplot	3
liliales	3
matrixcut	4
primates	5
xenarthra	5

Index	6
--------------	----------

componentplot	<i>Draws a Plot Showing the Number of Components as a Function of the Cutoff Value.</i>
---------------	---

Description

The function takes a square sequence similarity matrix and calculates the number of independent components in which the sequence similarity between the members is greater than a specified value (between 0 and 1). It creates a plots showing the number of components corresponding to a given cutoff value. The function also depicts the inflection point with a vertical line. Upper and lower bounds can be provided between which the inflection point will be found (if it exists).

Version 0.0.1. Author: Dr. Matthew Cserhati Email: csmaty@protonmail.com March 19, 2023

Arguments

mx	a square sequence similarity matrix
lower_bound	lower bounds for calculating the inflection point in, default = 0
upper_bound	upper bounds for calculating the inflection point in, default = 1

Value

A plot showing the number of components as a function of the cutoff threshold.

References

Mullner. <ArXiv:1109.2378>

Cserhati, Carter. (2020, Journal of Creation 34(3):41-50), <https://dl0.creation.com/articles/p137/c13759/j34-3_64-73.pdf>

Examples

```
componentplot(xenarthra,0.75,0.9)
componentplot(xenarthra)
```

cutoffplot	<i>Draws a Plot Showing the Number of Similarity Values as a Function of the Cutoff Value.</i>
------------	--

Description

The function takes a square sequence similarity matrix and creates a plot showing the number of similarity values above a given cutoff value, drawn on the x-axis, ranging from 0 to 1. The function also depicts the inflection point with a vertical line. Upper and lower bounds can be provided between which the inflection point will be found (if it exists).

Version 0.0.1. Author: Dr. Matthew Cserhati Email: csmaty@protonmail.com March 19, 2023

Arguments

mx	a square sequence similarity matrix
lower_bound	lower bounds for calculating the inflection point in, default = 0
upper_bound	upper bounds for calculating the inflection point in, default = 1

Value

A plot showing the number of similarity values as a function of the cutoff threshold.

References

Mullner. <ArXiv:1109.2378>

Cserhati, Carter. (2020, Journal of Creation 34(3):41-50), <https://dl0.creation.com/articles/p137/c13759/j34-3_64-73.pdf>

Examples

```
cutoffplot(liliales,0.7,0.85)
cutoffplot(liliales)
```

liliales	<i>Chloroplast genome sequence similarity matrix for 163 Liliales species</i>
----------	---

Description

Chloroplast genome sequence similarity matrix for 163 Liliales species

Usage

```
liliales
```

Format

```
## 'liliales' Chloroplast genome sequence similarity matrix for 163 Liliales species
```

matrixcut	<i>Calculates The Component Membership in a Sequence Similarity Matrix at a given Cutoff Value</i>
-----------	--

Description

The function takes a square sequence similarity matrix and calculates those independent components in which the sequence similarity between the members is greater than a specified value (between 0 and 1). The result provided by the function is a list of species with their component membership.

Version 0.0.1. Author: Dr. Matthew Cserhati Email: csmaty@protonmail.com March 19, 2023

Arguments

mx	a square sequence similarity matrix
cut	a given cutoff value to calculate components for, default value = -1

Value

The inflection point: cutoff value for the optimal number of clusters

A list of the species together with their cluster membership.

References

Mullner. <ArXiv:1109.2378>

Cserhati, Carter. (2020, Journal of Creation 34(3):41-50), <https://dl0.creation.com/articles/p137/c13759/j34-3_64-73.pdf>

Examples

```
matrixcut(primates, 0.8)  
matrixcut(primates)
```

primates	<i>Mitochondrial genome sequence similarity matrix for 31 primate species</i>
----------	---

Description

Mitochondrial genome sequence similarity matrix for 31 primate species

Usage

primates

Format

'primates' Mitochondrial genome sequence similarity matrix for 31 primate species

xenarthra	<i>Mitochondrial genome sequence similarity matrix for 37 Xenarthra species</i>
-----------	---

Description

Mitochondrial genome sequence similarity matrix for 37 Xenarthra species

Usage

xenarthra

Format

'xenarthra' Mitochondrial genome sequence similarity matrix for 37 Xenarthra species

Index

* datasets

liliales, 3

primates, 5

xenarthra, 5

componentplot, 2

cutoffplot, 3

liliales, 3

matrixcut, 4

primates, 5

xenarthra, 5